

Application

for

United States Patent

To all whom it may concern:

*Be it known that, David Engel, has invented certain new and useful improvements in*

***HOUSING APPARATUS AND METHOD FOR A MIXING  
APPARATUS***

*of which the following is a full, clear and exact description:*

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2224  
2225  
2226  
2227  
2228  
2229  
2230  
2231  
2232  
2233  
2234  
2235  
2236  
2237  
2238  
2239  
2240  
2241  
2242  
2243  
2244  
2245  
2246  
2247  
2248  
2249  
22410  
22411  
22412  
22413  
22414  
22415  
22416  
22417  
22418  
22419  
22420  
22421  
22422  
22423  
22424  
22425  
22426  
22427  
22428  
22429  
22430  
22431  
22432  
22433  
22434  
22435  
22436  
22437  
22438  
22439  
22440  
22441  
22442  
22443  
22444  
22445  
22446  
22447  
22448  
22449  
22450  
22451  
22452  
22453  
22454  
22455  
22456  
22457  
22458  
22459  
22460  
22461  
22462  
22463  
22464  
22465  
22466  
22467  
22468  
22469  
22470  
22471  
22472  
22473  
22474  
22475  
22476  
22477  
22478  
22479  
22480  
22481  
22482  
22483  
22484  
22485  
22486  
22487  
22488  
22489  
22490  
22491  
22492  
22493  
22494  
22495  
22496  
22497  
22498  
22499  
224100  
224101  
224102  
224103  
224104  
224105  
224106  
224107  
224108  
224109  
224110  
224111  
224112  
224113  
224114  
224115  
224116  
224117  
224118  
224119  
224120  
224121  
224122  
224123  
224124  
224125  
224126  
224127  
224128  
224129  
224130  
224131  
224132  
224133  
224134  
224135  
224136  
224137  
224138  
224139  
224140  
224141  
224142  
224143  
224144  
224145  
224146  
224147  
224148  
224149  
224150  
224151  
224152  
224153  
224154  
224155  
224156  
224157  
224158  
224159  
224160  
224161  
224162  
224163  
224164  
224165  
224166  
224167  
224168  
224169  
224170  
224171  
224172  
224173  
224174  
224175  
224176  
224177  
224178  
224179  
224180  
224181  
224182  
224183  
224184  
224185  
224186  
224187  
224188  
224189  
224190  
224191  
224192  
224193  
224194  
224195  
224196  
224197  
224198  
224199  
224200  
224201  
224202  
224203  
224204  
224205  
224206  
224207  
224208  
224209  
224210  
224211  
224212  
224213  
224214  
224215  
224216  
224217  
224218  
224219  
224220  
224221  
224222  
224223  
224224  
224225  
224226  
224227  
224228  
224229  
224230  
224231  
224232  
224233  
224234  
224235  
224236  
224237  
224238  
224239  
224240  
224241  
224242  
224243  
224244  
224245  
224246  
224247  
224248  
224249  
224250  
224251  
224252  
224253  
224254  
224255  
224256  
224257  
224258  
224259  
224260  
224261  
224262  
224263  
224264  
224265  
224266  
224267  
224268  
224269  
224270  
224271  
224272  
224273  
224274  
224275  
224276  
224277  
224278  
224279  
224280  
224281  
224282  
224283  
224284  
224285  
224286  
224287  
224288  
224289  
224290  
224291  
224292  
224293  
224294  
224295  
224296  
224297  
224298  
224299  
224300  
224301  
224302  
224303  
224304  
224305  
224306  
224307  
224308  
224309  
224310  
224311  
224312  
224313  
224314  
224315  
224316  
224317  
224318  
224319  
224320  
224321  
224322  
224323  
224324  
224325  
224326  
224327  
224328  
224329  
224330  
224331  
224332  
224333  
224334  
224335  
224336  
224337  
224338  
224339  
224340  
224341  
224342  
224343  
224344  
224345  
224346  
224347  
224348  
224349  
224350  
224351  
224352  
224353  
224354  
224355  
224356  
224357  
224358  
224359  
224360  
224361  
224362  
224363  
224364  
224365  
224366  
224367  
224368  
224369  
224370  
224371  
224372  
224373  
224374  
224375  
224376  
224377  
224378  
224379  
224380  
224381  
224382  
224383  
224384  
224385  
224386  
224387  
224388  
224389  
224390  
224391  
224392  
224393  
224394  
224395  
224396  
224397  
224398  
224399  
224400  
224401  
224402  
224403  
224404  
224405  
224406  
224407  
224408  
224409  
224410  
224411  
224412  
224413  
224414  
224415  
224416  
224417  
224418  
224419  
224420  
224421  
224422  
224423  
224424  
224425  
224426  
224427  
224428  
224429  
224430  
224431  
224432  
224433  
224434  
224435  
224436  
224437  
224438  
224439  
224440  
224441  
224442  
224443  
224444  
224445  
224446  
224447  
224448  
224449  
224450  
224451  
224452  
224453  
224454  
224455  
224456  
224457  
224458  
224459  
224460  
224461  
224462  
224463  
224464  
224465  
224466  
224467  
224468  
224469  
224470  
224471  
224472  
224473  
224474  
224475  
224476  
224477  
224478  
224479  
224480  
224481  
224482  
224483  
224484  
224485  
224486  
224487  
224488  
224489  
224490  
224491  
224492  
224493  
224494  
224495  
224496  
224497  
224498  
224499  
224500  
224501  
224502  
224503  
224504  
224505  
224506  
224507  
224508  
224509  
224510  
224511  
224512  
224513  
224514  
224515  
224516  
224517  
224518  
224519  
224520  
224521  
224522  
224523  
224524  
224525  
224526  
224527  
224528  
224529  
224530  
224531  
224532  
224533  
224534  
224535  
224536  
224537  
224538  
224539  
224540  
224541  
224542  
224543  
224544  
224545  
224546  
224547  
224548  
224549  
224550  
224551  
224552  
224553  
224554  
224555  
224556  
224557  
224558  
224559  
224560  
224561  
224562  
224563  
224564  
224565  
224566  
224567  
224568  
224569  
224570  
224571  
224572  
224573  
224574  
224575  
224576  
224577  
224578  
224579  
224580  
224581  
224582  
224583  
224584  
224585  
224586  
224587  
224588  
224589  
224590  
224591  
224592  
224593  
224594  
224595  
224596  
224597  
224598  
224599  
224600  
224601  
224602  
224603  
224604  
224605  
224606  
224607  
224608  
224609  
224610  
224611  
224612  
224613  
224614  
224615  
224616  
224617  
224618  
224619  
224620  
224621  
224622  
224623  
224624  
224625  
224626  
224627  
224628  
224629  
224630  
224631  
224632  
224633  
224634  
224635  
224636  
224637  
224638  
224639  
224640  
224641  
224642  
224643  
224644  
224645  
224646  
224647  
224648  
224649  
224650  
224651  
224652  
224653  
224654  
224655  
224656  
224657  
224658  
224659  
224660  
224661  
224662  
224663  
224664  
224665  
224666  
224667  
224668  
224669  
224670  
224671  
224672  
224673  
224674  
224675  
224676  
224677  
224678  
224679  
224680  
224681  
224682  
224683  
224684  
224685  
224686  
224687  
224688  
224689  
224690  
224691  
224692  
224693  
224694  
224695  
224696  
224697  
224698  
224699  
224700  
224701  
224702  
224703  
224704  
224705  
224706  
224707  
224708  
224709  
224710  
224711  
224712  
224713  
224714  
224715  
224716  
224717  
224718  
224719  
224720  
224721  
224722  
224723  
224724  
224725  
224726  
224727  
224728  
224729  
224730  
224731  
224732  
224733  
224734  
224735  
224736  
224737  
224738  
224739  
224740  
224741  
224742  
224743  
224744  
224745  
224746  
224747  
224748  
224749  
224750  
224751  
224752  
224753  
224754  
224755  
224756  
224757  
224758  
224759  
224760  
224761  
224762  
224763  
224764  
224765  
224766  
224767  
224768  
224769  
224770  
224771  
224772  
224773  
224774  
224775  
224776  
224777  
224778  
224779  
224780  
224781  
224782  
224783  
224784  
224785  
224786  
224787  
224788  
224789  
224790  
224791  
224792  
224793  
224794  
224795  
224796  
224797  
224798  
224799  
224800  
224801  
224802  
224803  
224804  
224805  
224806  
224807  
224808  
224809  
224810  
224811  
224812  
224813  
224814  
224815  
224816  
224817  
224818  
224819  
224820  
224821  
224822  
224823  
224824  
224825  
224826  
224827  
224828  
224829  
224830  
224831  
224832  
224833  
224834  
224835  
224836  
224837  
224838  
224839  
224840  
224841  
224842  
224843  
224844  
224845  
224846  
224847  
224848  
224849  
224850  
224851  
224852  
224853  
224854  
224855  
224856  
224857  
224858  
224859  
224860  
224861  
224862  
224863  
224864  
224865  
224866  
224867  
224868  
224869  
224870  
224871  
224872  
224873  
224874  
224875  
224876  
224877  
224878  
224879  
224880  
224881  
224882  
224883  
224884  
224885  
224886  
224887  
224888  
224889  
224890  
224891  
224892  
224893  
224894  
224895  
224896  
224897  
224898  
224899  
224900  
224901  
224902  
224903  
224904  
224905  
224906  
224907  
224908  
224909  
224910  
224911  
224912  
224913  
224914  
224915  
224916  
224917  
224918  
224919  
224920  
224921  
224922  
224923  
224924  
224925  
224926  
224927  
224928  
224929  
224930  
224931  
224932  
224933  
224934  
224935  
224936  
224937  
224938  
224939  
224940  
224941  
224942  
224943  
224944  
224945  
224946  
224947  
224948  
224949  
224950  
224951  
224952  
224953  
224954  
224955  
224956  
224957  
224958  
224959  
224960  
224961  
224962  
224963  
224964  
224965  
224966  
224967  
224968  
224969  
224970  
224971  
224972  
224973  
224974  
224975  
224976  
224977  
224978  
224979  
224980  
224981  
224982  
224983  
224984  
224985  
224986  
224987  
224988  
224989  
224990  
224991  
224992  
224993  
224994  
224995  
224996  
224997  
224998  
224999  
2249999

**HOUSING APPARATUS AND METHOD FOR A MIXING APPARATUS****PRIORITY**

[0001] This application claims priority to the provisional U.S. Patent Application entitled, STAINLESS STEEL MIXING APPARATUS AND METHOD, filed October 25, 2001, having a serial number 60/330,579, the disclosure of which is hereby incorporated by reference.

**FIELD OF THE INVENTION**

[0002] The present invention relates generally to a method and apparatus for mixer components for use in e.g., sterile mixing applications. More particularly, the present invention relates to a method and apparatus for providing a cover over a drive component of a mixer.

**BACKGROUND OF THE INVENTION**

[0003] There are many circumstances where it is necessary to effect the mixing of materials under very sanitary conditions. These circumstances include, for example, the production of food products, the production of pharmaceutical products, the production of mineral products and the production of chemical products. The materials to be mixed can be of many forms such as mixed powders, wet granules, pastes, slurries and/or liquids. In order to attain the desired degree of sanitary environment, many manufacturers and producers of the aforementioned products employ stainless steel in the components of mixers in their manufacturing and production processes.

[0004] In the food industry, for example, stainless steel mixers are utilized to transform powdery materials into agglomerated products in order to instantize these

products. Stainless steel mixers are also used to produce many of the ingredients contained within food products. In addition, ready-to-eat food products are mixed and manufactured using stainless steel mixers.

[0005] In the pharmaceutical industry, for example, stainless steel mixers are used to transform powdered pharmaceutical compounds into free flowing pastes prior to being fed into tableting machines. Stainless steel mixers are additionally used to produce homogeneous pharmaceutical mixtures by mixing multiple liquid pharmaceutical compounds together.

[0006] Stainless steel is utilized because the above-described processes are preferably and frequently required to be carried out according to stringent sanitary requirements. Stainless steel allows minimum contaminant accumulation on the mixer surfaces. This is due to the fact that stainless steel is easily cleaned and resistant to corrosion. Many mixers present in the art currently use stainless steel components in their mixer assemblies. These components range from stainless steel motors and shafts to mixing vessels and speed reducers. These mixers and mixer components have drawbacks however.

[0007] The cost of using stainless steel to manufacture mixers and mixer components is significantly high when compared to using conventional materials such as iron or steel. As a result of this high cost, the mixer purchase price is substantially higher than that of standard mixers. Due to this high purchase price, the cost of manufacturing and producing products with these stainless steel mixers increases. The cost is particularly noticeable in the case of drive components such as motors and/or speed reducers, which have a large number of complex parts. It is very expensive, for

example, to manufacture a speed reducer so that all the exposed parts are made of stainless steel.

[0008] Accordingly, it is desirable to provide a housing for covering a drive system components for use in sanitary mixing applications. More particularly, there is a need for a housing that encloses a drive component such as a mixer gearbox and/or speed reducer, so that the gearbox and/or speed reducer has its exposed surfaces made of a material that is easily cleanable and/or resists corrosion, but at a significantly lower cost.

#### SUMMARY OF THE INVENTION

[0009] The foregoing needs are met, to a great extent, by the present invention where, in one aspect, a housing is provided for covering a portion of a drive component. The housing includes a cover and at least one support that supports the cover on drive component.

[0010] In accordance with another aspect of the present invention, a housing is provided for covering a portion of a drive component that has a cover and a sealing element that seals the cover to the drive component.

[0011] In accordance with yet another aspect of the present invention, a mixing apparatus is provided having a motor assembly and a mixing vessel configured for receiving material to be mixed. The mixing apparatus additionally includes a seal pedestal connected to the mixing vessel and a cover that is supported between the motor assembly and the seal pedestal, that covers at least part of a drive component connected between the motor assembly and seal pedestal.

[0012] In yet another aspect, the invention provides a method for covering at least a portion of a drive assembly. This method includes the steps of covering a portion of a drive component with a cover, and supporting the cover with at least one support.

[0013] In still another aspect, the invention provides a method for sealing at least a portion of a drive assembly. This method includes the steps of covering a portion of the drive component with a cover, and sealing the cover to the drive assembly.

[0014] There has thus been outlined, rather broadly, certain features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are, of course, additional features of the invention that will be described below and which will form the subject matter of the claims appended hereto.

[0015] In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein, as well as the abstract, are for the purpose of description and should not be regarded as limiting.

[0016] As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such

equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] FIG. 1 is a schematic cross-sectional view of a housing assembly in accordance with the present invention in operational relationship with a drive component of a mixer.

[0018] FIG. 2 is a cross-sectional view of a speed reducer employing a housing in accordance with the present invention.

[0019] FIG. 3 is a top view of a cover in accordance with the present invention.

[0020] FIG. 4 is a side view of a mixer assembly employing a housing in accordance with the present invention.

[0021] FIG. 5 is a cross-sectional view of a housing assembly in accordance with two alternative embodiments of the present invention.

DETAILED DESCRIPTION OF PREFERRED  
EMBODIMENTS OF THE INVENTION

[0022] The present invention provides a housing for disposing mixer drive components within a cover that can be made of a material that is easily cleanable and/or resists corrosion. The housing may preferably used in combination with a speed reducer for a mixer. It should be understood, however, that the present invention is not limited in its application to mixer speed reducers, but for example, can be used with other devices and/or drive components. The invention is particularly useful in sanitary processes, but can also be used in other processes.

[0023] Referring now to the figures wherein like reference numerals indicate like elements, FIGS. 1-5 illustrate presently preferred embodiments of a housing assembly. While in the embodiment depicted the housing assembly is utilized in combination with a drive assembly of a mixer, it should also be understood that the present invention is not limited in its application to mixer drive assemblies, and can be used for other types of drive devices including, for example, motors and transmissions or other mechanical devices.

[0024] FIGS. 1 and 2 depict cross-sectional views of a mixer drive assembly 10 having a first, upper portion 12, a second, middle portion 14, and a third, lower portion 16. More particularly, in the illustrated embodiment 10 the upper portion 12 includes a motor assembly, the middle portion 14 includes a speed reducer, and the lower portion 16 includes a seal pedestal. The speed reducer 14 is placed between the motor assembly 12 and the seal pedestal 16. The speed reducer 14 is affixed to the motor assembly 12 by an affixing means such as a screw or bolt 18 and the speed reducer 14 is affixed to the seal pedestal 16 utilizing a clamp such as a Tri-clamp® 18. The apparatus 10 also includes a cover 20, a first sealing element 26, a second sealing element 28, a first support 22, and a second support 24.

[0025] The supports 22 and 24 are preferably provided by flanges in the speed reducer 14. The first flange 22 has a diameter preferably greater than the diameter of the cover 20. The first flange 22 is preferably formed from a material that is easily cleanable and resists corrosion, for example, stainless steel, since it is exposed to the surrounding environment. The first flange 22 has a shoulder 23 upon which a first sealing element 26 is disposed. The second, flange 24 preferably has a diameter that is less than the diameter

of the cover 20. The upper flange 24 also has a shoulder 25 upon a which a second sealing element 28 is disposed.

**[0026]** Sealing elements 26 and 28 are preferably elastomeric O-rings, however alternative sealing elements may be employed. As illustrated, O-ring 26 is disposed upon the shoulder 23 of the flange 22 and contacts both the cover 20 and the face 23A of the shoulder 23. Preferably, the O-ring 26 is positioned such that the cover 20 is radially supported by the O-ring 26 and does not touch the flange 22 or have any load-bearing contact the flange 22. However, the end of cover 20 may in some embodiments touch the shoulder 23 to rest on the shoulder 23 with a minimal load. The O-ring 26 exerts a slight radial force on both the shoulder 23 and the cover 20. This force provides sealing engagement between the flange 22 and the cover 20. This radial force can also tend to inhibit axial motion of the cover 20. The O-ring 26 is illustrated touching face 23A and not touching face 23B. However, the O-ring 26 may also touch the face 23B.

**[0027]** O-ring 28 is disposed upon the shoulder 25 of the flange 24. Preferably, the O-ring 28 is positioned such that the cover 20 is radially supported by the O-ring 28 and does not contact the motor assembly 12 with any load bearing contact. However, the end of cover 20 may in some embodiments touch the end of the motor assembly 12 to rest against the motor assembly with a minimal load. The O-ring 28 exerts a slight radial force on both the flange 24 and the cover 20, providing sealing engagement between the flange 24 and the cover 20. This radial force also tends to inhibit axial motion of the cover 20. The O-ring 26 is illustrated touching face 23A and not touching face 23B. However, the O-ring 26 may also touch the face 23B.

[0028] The aforementioned sealing engagement between the flanges 22 and 24 the O-rings 26 and 28, and the cover 20 affords the interior atmosphere of the speed reducer 14 to be isolated from the outside mixer environment, which is desirable when the mixer is operating under sanitary conditions. In addition, these parts are dimensioned to allow for the upper and lower flanges, 24 and 22 respectively, to confine the cover 20 between these respective supports so that it floats between them and does not carry any significant load.

[0029] Referring now to FIG. 3, looking at a top view of cover 20, the cover 20 includes a curved side wall 30. As illustrated in FIGS. 1 and 2, the cover 20 has one end that is adjacent the motor assembly 12 when installed and another end that is adjacent the seal pedestal 16 when installed, and the cover 20 extends between the base of the motor assembly 12 and the flange 22. The motor assembly 12 is located above the stainless steel cover 20 where it acts as an "upper stop" to the cover 20. The flange 22 is located at a lower portion of the speed reducer 14, and acts as a "lower stop" to the cover 20.

[0030] In the embodiment depicted, the cover 20 is cylindrical in shape, preferably, a hollow cylinder. In addition, the cover 20 is preferably formed from a cleanable, corrosive-resistant material, such as for example stainless steel. More particularly, the cover 20 is constructed from six-inch welded stainless steel pipe for example. Preferably, the length of the cover 20 is tolerated to be less than the axial length between face 23B of the speed reducer and the end 29 of the motor, preventing the cover 20 from contacting the face 23B and the end 29 at the same time. This prevents an undesirable degree of axial compressive load from being put on the cover 20.

[0031] As further illustrated by FIG. 1, the stainless steel cover 20 preferably rests on the O-ring 26, providing a lower sealing means for the cover 20. The cover 20 additionally rests on the O-ring 28, providing an upper sealing means for the cover 20. The above-described interaction between the stainless steel cover 20 and the O-rings 26, 28 allows for the stainless steel cover 20 to float with respect to the speed reducer assembly 14, and in some embodiments not touch either the motor 12 or flange 22. Thus, the cover 20 does not need to carry any significant axial load. In addition, the cover 20 also receives some radial outward forces from the O-rings 26 and 28. The O-rings 26 and 28 also tend to inhibit axial movement of the cover 20 to a limited degree.

[0032] Alternatively, an end of the cover 20 may directly contact either one of the motor assembly 12 or the flange 22 and therefore not completely float between the two supports. However, the cover 20 is toleranced so that it does not extend the entire distance between the motor assembly 12 and the flange 22. The resting position of the cover is determinative of whether a gap exists between the cover 20 and the motor assembly 12, or exists between the cover 20 and the flange 22. For example, if the cover 20 rests on the flange 22, a gap exists between the cover 20 and the motor assembly 12 and vice versa. However, even though the cover may directly contact one of the flange 22 or the motor assembly 12, the cover 20 again does not function as a structural component and therefore does not carry any significant load.

[0033] As previously described, the flange 22 can function both (1) as an axial positioning element or stop and (2) as a radial supporting element via O-ring 26. The flange 22 is utilized in combination with a clamp 18, preferably a Tri-Clamp® to affix the speed reducer 14 to a seal pedestal 16. In another aspect, as described above, the flange 22 in combination with the O-ring 26, functions as a lower stop or axial

positioning element for the stainless steel cover 20, allowing the cover 20 to remain in a stationary axial position, between the motor assembly 12 and the flange 22.

**[0034]** A function of the O-rings 26 and 28 is to provide a sealing arrangement for the stainless steel cover 20, in addition to providing some radial support as described above. This sealing arrangement allows for components such as a speed reducer to be disposed with the stainless steel cover 20, and be sealed within the cover 20, effectively preventing exposure of the components to the outside environment. This sealing allows the components contained within the cover 20 to function during mixer operation without contaminating the outside environment with operating fluids and/or foreign particles. Therefore, the environment outside the mixer remains sanitary which is desirable for many mixer applications. In addition, the sealing allows the cover 20 to be cleaned easily, without any need to clean the components contained inside the cover 20.

**[0035]** FIG. 2 shows a conventional, concentric speed reducer 14 disposed within the stainless steel cover 20. Preferably, the speed reducer 14 as illustrated is a reducer having a desirably small outer diameter, such as an epicyclic reducer or a planetary reducer. A conventional speed reducer and its components may be modified by reducing the concentric reducer's diameter, length and width to fit within a suitable cover dimension if needed. For example, the outer diameter of the speed reducer can be decreased by machining the reducer's frame which also translates into a reduced width. The overall length of the speed reducer can be shortened by closely coupling the speed reducer assembly to the mixer motor assembly. The speed reducer can also be coupled to the motor assembly without the assistance of a flexible coupler element placed between the motor and reducer assemblies, to decrease the reducer length. Of course, the

cover may also be made of a suitable size to cover larger speed reducers or other components.

[0036] The cover 20 is not limited in its application to mixer speed reducers. Alternatively, the cover 20 may be utilized to house various mixing drive assembly components that may be used under sanitary conditions. For example, the cover 20 may be used to cover standard drive shafts, motors and/or gear assemblies of driven rotating devices. The cover 20 may be used to cover any drive system components, speed reducers, drive shafts, bearings, motors, seal cartridges.

[0037] Although in the preferred embodiment a cylindrical cover 20 is described, alternatively configured cover designs may be employed. For example, the assembly may utilize a cover wherein the side walls are not circular but form a shape similar to that of a square or rectangle. In addition, the assembly may utilize a cover wherein the side walls taper toward each other, forming a shape similar to that of a cone.

[0038] Referring now to FIG. 4, a mixer assembly 40 is illustrated employing the cover 20 of the present invention. The mixer assembly 40 includes a driving means 42 such as a motor or turbine attached to a gear assembly 44 such as a speed reducer or gear box. The mixer assembly 40 also includes a mixing vessel 46 configured for containing the material to be mixed. As illustrated, the cover 20 is restrained between the driving means 42 and the seal pedestal 45 of the mixing vessel 46. The speed reducer 44 is surrounded by the stainless cover 20. The mixer assembly additionally includes a rotatable shaft 48 extending from the driving means 42 and speed reducer 34 into the mixing vessel 46. The rotatable shaft 48 may be connected to an impeller shaft 47 to rotate an impeller 49.

[0039] The speed reducer 44 illustrated in FIG. 4 is preferably a conventional, concentric speed reducer reconfigured such that it may be disposed within the cylindrical stainless steel cover 20. However, standard speed reducers may also be used in combination with the present invention.

[0040] Although the cover 20 is described as being stainless steel, the cover can be made of other materials. For example, the cover can be made of other metals, alloys, plastics and/or ceramics.

[0041] Referring now to FIG. 5, an alternative embodiment 50 in accordance with the present invention is depicted. The illustrated alternative embodiment is similar to previously described embodiments, except for the interaction between the O-rings and the flanges. The O-ring 60 is disposed within a shoulder 54 located on the mixer motor assembly 56, instead of shoulder 25 (FIGS. 1 and 2), which can be omitted. This configuration illustrates that the sealing elements of the present invention can be supported on a component adjacent the drive component being covered by the cover 58, or supported by the drive component itself. The O-rings 62 can be a set of adjacent O-rings supported by a flange 64. The use of plural stacked O-rings 62 can provide enhanced resistance to vertical movement of the cover 58, so that the shoulder 64 can have a outer diameter less than the inner diameter of the cover 58, and the cover 58 can extend down over the shoulder 64. This illustrates that the O-rings themselves can serve instead of a stop in the axial direction.

[0042] The many features and advantages of the invention are apparent from the detailed specification, and thus, it is intended by the appended claims to cover all such features and advantages of the invention which fall within the true spirit and scope of the invention. Further, since numerous modifications and variations will readily occur to

those skilled in the art, it is not desired to limit the invention to the exact construction and operation illustrated and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

2022007077920